



EBGEL      Aerosol Metal, 15 oz.  
078698216041

## ENGINE DEGREASER HEAVY DUTY GEL

**GUNK® Heavy Duty Gel, Our Best Engine Degreaser, is specially formulated to remove baked on grease and oil from hotter-running engines. GUNK® Heavy Duty Gel clings to the engine surface being sprayed and does not run off. Since the product stays where it's sprayed, it has more time to penetrate baked on engine soils. Heavy duty degreasing formula for Cars, Trucks, Power Mowers, Marine, Heavy-Duty Rigs, Farm Equipment and Tractors as well as Industrial Machinery. Clean your Engine with GUNK® Heavy Duty Gel and then protect it with GUNK® Shine.**

**BENEFITS:** Our most aggressive engine degreaser • For hotter running, older engines • Clings to eliminate baked on grease • Deep penetrating action • No scrubbing required • Rinses clean with water

**DIRECTIONS:** Do not start your engine after you have applied GUNK® Heavy Duty Gel until entire engine is properly rinsed. Rinsing is necessary to properly clean engine and to avoid potential fire hazard. SAFEGUARD OUR ENVIRONMENT. USE THE MINIMUM AMOUNT OF RINSE WATER NECESSARY AND SEE DISPOSAL STATEMENT BELOW. 1. Engine must be off and cool. 2. Care must be taken with all underhood wiring and electronic sensors or components. Cover any open carburetor or intake system openings. Cover exposed electrical and electronic components (uncovered cracked, frayed wires or engine computer units can short circuit). 3. Shake well and apply generously to dry engine. Make sure to cover all dirty and greasy surface areas with GUNK® Heavy Duty Gel. Wipe overspray from exterior body surfaces with a wet cloth quickly to avoid de-waxing or streaking paint. 4. Allow GUNK® Heavy Duty Gel to soak for 10 to 15 minutes. Brush unusually heavy deposits to break up grease and dirt. 5. Rinse all areas with a fine stream of water from top down. Minimize rinse water in areas that can cause performance problems (electronics & intakes). 6. When complete, remove added coverings and replace any removed parts. Start engine and idle 15 minutes to assure complete drying. Avoid use of GUNK® Heavy Duty Gel on tile, asphalt, black top, or other surfaces affected by petroleum solvents.

**STORAGE, HANDLING & DISPOSAL:** Contents under pressure. Use with proper ventilation. Store in a cool, dry area. Do not puncture, crush or incinerate container or store above 120°F (48°C). Do not expose contents or put container into contact with heat, sparks, open flame, or electrical connections or battery terminals. The residue resulting from the removal of petroleum oils and greases may be considered a hazardous waste depending upon where and how generated. The use of this product to clean engines and bilges in watercraft produces a hazardous waste that cannot be discharged into any waterway. Disposal of contaminated rinse water into watercourses, sewers, or on the ground may also be prohibited by law. Such disposal is prohibited in California. Proper disposal includes collecting and evaporating rinse water and/or recycling and disposal of residues and the empty container in accordance with all local, state, and federal laws and regulations.

**DANGER:** Harmful or fatal if swallowed. Use only in a well-ventilated area. Deliberately inhaling concentrated vapors can be harmful or fatal. Avoid contact with eyes and skin. Keep away from heat, sparks, and open flame.

**FIRST AID:** EYE CONTACT: Flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. SKIN CONTACT: Wash with soap and water. If irritation develops, get prompt medical attention. INHALATION: Move to fresh air. If breathing becomes difficult, get prompt medical attention. INGESTION: DO NOT INDUCE VOMITING. Call Poison Control Center, Physician or Hospital Emergency Room immediately.

**KEEP AWAY FROM CHILDREN AND ANIMALS**

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.